

## **IPTC 13765 - PP**

# **Successful Field Application of an Inhibitor Concentration Detection System in Optimising the Kinetic Hydrate Inhibitor (KHI) Injection Rates and Reducing the Risks Associated with Hydrate Blockage**

Orlin Lavallie, Ahmed Al Ansari, Stephen O'Neil and Olivier Chazelas, Dolphin Energy Limited, Doha, Qatar  
Philippe Glénat, SPE, Total E&P, Pau, France  
Bahman Tohidi, SPE, Hydract Ltd., Edinburgh, Scotland, UK

Copyright 2009, International Petroleum Technology Conference

This paper was prepared for presentation at the International Petroleum Technology Conference held in Doha, Qatar, 7–9 December 2009.

This paper was selected for presentation by an IPTC Programme Committee following review of information contained in an abstract submitted by the author(s). Contents of the paper, as presented, have not been reviewed by the International Petroleum Technology Conference and are subject to correction by the author(s). The material, as presented, does not necessarily reflect any position of the International Petroleum Technology Conference, its officers, or members. Papers presented at IPTC are subject to publication review by Sponsor Society Committees of IPTC. Electronic reproduction, distribution, or storage of any part of this paper for commercial purposes without the written consent of the International Petroleum Technology Conference is prohibited. Permission to reproduce in print is restricted to an abstract of not more than 300 words; illustrations may not be copied. The abstract must contain conspicuous acknowledgment of where and by whom the paper was presented. Write Librarian, IPTC, P.O. Box 833836, Richardson, TX 75083-3836, U.S.A., fax +1-972-952-9435.

---

### **Abstract**

Currently, hydrate inhibitors are injected at the pipelines upstream based on the calculated/measured hydrate phase boundary, water cut, worst pressure and temperature conditions, and the amount of inhibitor lost to non-aqueous phases. In general, no means of controlling and monitoring are available along the pipeline and/or downstream to assess the degree of inhibition. Often high safety margins are considered to accommodate for the uncertainties in the above parameters and to ensure gas hydrate risks are eliminated. However, despite these efforts hydrates do still form and this can result in considerable economical and safety concerns.

As a result of a joint industry project, a novel device based on electrical conductivity and sonic velocity (C-V technique) has been developed for monitoring the hydrate safety margin to optimise inhibitor injection rates. The system determines the amount of inhibitors (e.g., salt, KHI, methanol, MEG, etc...) in the aqueous phase and the degree of inhibition they can provide.

The device has been successfully applied in determining the amount of KHI in produced water from the Dolphin field in Qatar. Compared to conventional chemical techniques the device is much faster (less than 3 minutes) and less labour intensive and there is no chemical requirement.

In this presentation, the results of the trial of this device in determining KHI concentration in produced water are described. The results shows that this new technique is very fast and reliable, optimising the KHI injection rate, improving the economy and reliability of hydrate inhibition strategy, and minimising the impact on the environment.